

# RENAULT (EU) MAXITY MAXITY 150 DXI + DPF (2010-2014)

**ENGINE DXi 3 (ZD3 A600)**

Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Meganza LSP 5W-30***Change every 20000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

## PRODUCT RECOMMENDATION 1

**Meganza LSP 5W-30***Change every 10000 km/ 12 months***DIFFERENTIAL REAR H260**

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 60000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 30000 km/ 24 months***DIFFERENTIAL REAR H290**

Capacity: 5,1 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 60000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 30000 km/ 24 months*

# RENAULT (EU) MAXITY MAXITY 150 DXI + DPF (2010-2014)



## POWER TAKE OFF

Capacity: 0,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## TRANSMISSION MANUAL ZF 6S-380 6/1

Capacity: 2,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## HYDRAULIC BRAKE/CLUTCH SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

## POWER STEERING

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

## COOLING SYSTEM

Capacity: 12,5 liter, Capacity: 13,2 liter (+ rear heater)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 16**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*