

# RENAULT (EU) TRAFIC TRAFIC P 800, P 1000, P 1200 1.4 (1986-1989)

**ENGINE 847/CJ1**

Capacity: 3 liter, Filter capacity: 0,25 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SHPD 15W-40</b>	<b>Multifleet SHPD 20W-50</b>	

*Change every 7500 km*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 5W-40</b>	<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>

*Change every 7500 km*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>Asyntho 5W-30</b>		

*Change every 7500 km***DIFFERENTIAL REAR (4x2)**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Check every 10000 km, change every 50000 km***TRANSMISSION MANUAL 4/1**

Capacity: 2,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 5015</b>	<b>Gearlube RPC 75W-80</b>	<b>SP Gear 1071</b>

*Check every 10000 km, change every 50000 km*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>SP Gear 1081</b>		

*Check every 10000 km, change every 50000 km*

# RENAULT (EU) TRAFIC TRAFIC P 800, P 1000, P 1200 1.4 (1986-1989)



## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 50000 km*

## COOLING SYSTEM

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 50000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*