

**SUZUKI CARRY CARRY (1990-1994)****ENGINE F8A**

Capacity: 3,5 liter, Filter capacity: 0,25 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40**

## PRODUCT RECOMMENDATION 3

**Asyntho 5W-30***Change every 10000 km/ 6 months***DIFFERENTIAL REAR (4x2)**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**SP Gear 1071**

## PRODUCT RECOMMENDATION 3

**Syngear TDL 75W-90***Check every 10000 km/ 6 months, change every 40000 km/ 24 months***TRANSMISSION MANUAL 4/1**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015**

## PRODUCT RECOMMENDATION 3

**Syngear MT/LD 75W-80***Check every 10000 km/ 6 months, change every 40000 km/ 24 months***TRANSMISSION MANUAL 5/1**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015**

## PRODUCT RECOMMENDATION 3

**Syngear MT/LD 75W-80***Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

**SUZUKI CARRY CARRY (1990-1994)****HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Change every 40000 km/ 48 months*

**COOLING SYSTEM**

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 40000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*