

TOYOTA (EU) HI-ACE HI-ACE 2.5 D-4D

EURO 4 (86 KW) (4X2) (4X2) (2007-2012)

**ENGINE 2KD-FTV**

Capacity: 7,2 liter (Dry fill), Capacity: 6,5 liter (Service fill), Filter capacity: 0,2 liter

| USE | CLIMATE |
|----------------------|---------------|
| Normal (alternative) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|-------------------------------|
| Bi-Turbo 15W-40 | Bi-Turbo 20W-50 | Dieselfleet CD+ 15W-40 |

Change every 15000 km

| USE | CLIMATE |
|----------------------|----------|
| Normal (alternative) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|-----------------------------|
| Asyntho 5W-30 | Emperol 10W-40 | Synfleet SHPD 10W-40 |

Change every 15000 km

| USE | CLIMATE |
|--------------------|---------------|
| Normal (preferred) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|-------------------------------|
| Bi-Turbo 15W-40 | Bi-Turbo 20W-50 | Dieselfleet CD+ 15W-40 |

Change every 15000 km

| USE | CLIMATE |
|--------------------|----------|
| Normal (preferred) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|-----------------------------|
| Asyntho 5W-30 | Emperol 10W-40 | Synfleet SHPD 10W-40 |

Change every 15000 km

| USE | CLIMATE |
|--------------------|---------|
| Normal (preferred) | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|---------------------------|--|
| Duranza LSP 5W-30 | Armado Synth 5W-30 | |

*Change every 15000 km***DIFFERENTIAL REAR**

Capacity: 1,25 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |

Change every 30000 km

TOYOTA (EU) HI-ACE HI-ACE 2.5 D-4D

EURO 4 (86 KW) (4X2) (4X2) (2007-2012)



DIFFERENTIAL REAR LIMITED SLIP

Capacity: 1,25 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 30000 km*

TRANSMISSION AUTOMATIC 4/1

Capacity: 1,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 4026*Check every 30000 km, change every 90000 km*

TRANSMISSION MANUAL G56 5/1

Capacity: 2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 60000 km*

TRANSMISSION MANUAL R151 5/1

Capacity: 2,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 60000 km*

HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 30000 km*

TOYOTA (EU) HI-ACE HI-ACE 2.5 D-4D

EURO 4 (86 KW) (4X2) (4X2) (2007-2012)



POWER STEERING

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |

Change every 30000 km

COOLING SYSTEM

Capacity: 8,8-12 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |

Change every 30000 km

| USE | | CLIMATE |
|--------------------------|--|----------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |

Change every 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.