TOYOTA (USA / CAN) TUNDRA TUNDRA 4.0 V6 24V (USA) GSK50/51 (2007-2010)



ENGINE 1GR-FE Capacity: 6 liter (Dry fill), Capacity: 5,2 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Presteza MSP 5W-30				
Change every 5000 miles/ 6 months				
DIFFERENTIAL REAR				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 1071				
Check every 15000 miles/ 18 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 1071				
Change every 15000 miles/ 18 months				
TRANSMISSION AUTOMATIC A750E 5/1 Capacity: 10,5 liter (Dry fill), Capacity: 3 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 30000 miles/ 36 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				

Check every 30000 miles/36 months, change every 60000 miles/72 months

TOYOTA (USA / CAN) TUNDRA TUNDRA 4.0 V6 24V (USA) GSK50/51 (2007-2010)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 5000 miles/ 6 months	

POWER STEERING Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Check every 5000 miles/ 6 months	'	,

COOLING SYSTEM Capacity: 9,6 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months				
USE		CLIMATE		
First change only		Moderate		

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

PRODUCT RECOMMENDATION 1

Coolant SP 14+