VAUXHALL VIVARO B X82 VIVARO B 1.6 CDTI (66 KW) (2014-2016)



		!
Helar SP LL-03 5W-30	Presteza MSP 5W-30	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
ENGINE R9M 408 (LWX, LWZ) Capacity: 6 liter		

Change every 40000 km/ 12 months

TRANSAXLE MANUAL PF6 6/1 Capacity: 2,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 40000 km/ 12 months	•	

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Charle avany 40000 km/24 months, abanga ayany 120000 km	

Check every 40000 km/24 months, change every 120000 km/48 months

POWER STEERING Capacity: 0-0 liter (Between min and max.)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 40000 km/ 12 months	'			

COOLING SYSTEM Capacity: 8,3 liter, Capacity: 9,9 liter (+ additional heater + pre-heater)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant SP 15	Coolant SP 15+			

Check every 40000 km/24 months, change every 160000 km/72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

VAUXHALL VIVARO B X82 VIVARO B 1.6 CDTI (66 KW) (2014-2016)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.