HYDRAULIC BRAKE SYSTEM

Capacity: 1,25 liter

VOLKSWAGEN (VW) (EU) CADDY 2K/2C CADDY 2.0 TDI (125 KW) DPF (2012-2015)



ENGINE CFJA Capacity: 4,3 liter	
USE	CLIMATE
Extended drain (max)	Moderate
PRODUCT RECOMMENDATION 1	
Helar SP LL-03 5W-30	
Change every 30000 km/24 months	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Helar SP LL-03 5W-30	
Change every 15000 km/ 12 months	

TRANSAXLE SEMI-AUTOMATIC DSG 02E (DQ250) 6/1 Capacity: 7,2 liter (Dry fill), Capacity: 5,2 liter (Service fill)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Matic 2072				
Change every 60000 km/ 48 months	·			

1 7 7	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 36 months	·

VOLKSWAGEN (VW) (EU) CADDY 2K/2C CADDY 2.0 TDI (125 KW) DPF (2012-2015)



POWER STEERING				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Fluid 3013				

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Coolant SP 12 EVO			
Check every 48 months/ 60000 km			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.