

VOLKSWAGEN (VW) (EU) LT LT 28(A) 2.5 TDI (1996-1999)

**ENGINE AHD**

Capacity: 7,8 liter, Filter capacity: 1 liter

| USE | | CLIMATE |
|---------------------------|-------------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Presteza MSP 5W-30 | Specialsynth MSP 5W-40 | Emperol 5W-50 |

Change every 22500 km/ 12 months

| USE | | CLIMATE |
|--------------------------|--|---------|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Emperol 5W-40 | | |

*Change every 22500 km/ 12 months***DIFFERENTIAL REAR (4x2)**

Capacity: 1,5 liter

| USE | | CLIMATE |
|--------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1011 | Syngear TDL 75W-90 | |

*Check every 45000 km, change every 90000 km***TRANSMISSION MANUAL 5/1**

Capacity: 2,2 liter

| USE | | CLIMATE |
|--------------------------|---------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |

*Check every 45000 km, change every 90000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 2 liter

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Change every 24 months

VOLKSWAGEN (VW) (EU) LT LT 28(A) 2.5 TDI (1996-1999)



POWER STEERING

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 4026 | SP Matic 2032 | |

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 48 months

COOLING SYSTEM

Capacity: 13 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.