DODGE RAM (USA / CAN) SPRINTER GEN II SPRINTER 3500 3.5 V6 (2006-2008)



ENGINE M272 E35 Capacity: 9,5 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

Change every 100000 miles/ 12 months

DIFFERENTIAL REAR Capacity: 1,6-2,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
Observed 4000000 mails at 4000 m		3

Change every 180000 miles/ 120 months

TRANSMISSION AUTOMATIC 722.6xx 5/1 Capacity: 5,5-7,1 liter			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
Change every 60000 miles/ 120 months	'		

HYDRAULIC BRAKE SYSTEM ABS	
Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE

Normal Moderate
PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

Change every 24 months

POWER STEERING Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4026	SP Matic 2032		

PRODUCT RECOMMENDATION

DODGE RAM (USA / CAN) SPRINTER GEN II SPRINTER 3500 3.5 V6 (2006-2008)



COOLING SYSTEM Capacity: 7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 11			
Check every 12 months, change every 100000 miles/ 60 months			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 11			
Check every 12 months, change every 180000 miles/ 180 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.