

IVECO DAILY / TURBODAILY TURBODAILY

49.12 (1996-1999)

**ENGINE 8140.43.37**

Capacity: 7 liter, Filter capacity: 1,1 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	

Change every 20000 km/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Bi-Turbo 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40

Change every 20000 km/ 12 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 20000 km/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

*Change every 20000 km/ 12 months***DIFFERENTIAL REAR 4517**

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 20000 km, change every 60000 km/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 20000 km, change every 60000 km/ 12 months

IVECO DAILY / TURBODAILY TURBODAILY

49.12 (1996-1999)



TRANSMISSION MANUAL 5/1

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 20000 km, change every 60000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 12 months

POWER STEERING ZF 8090

Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

GREASE POINTS/NIPPLES BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	Multi Purpose Grease 3	

Check every 20000 km/ 12 months

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 20000 km/ 12 months

IVECO DAILY / TURBODAILY TURBODAILY

49.12 (1996-1999)

**COOLING SYSTEM**

Capacity: 13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 120000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.