

KIA (EU) K SERIES K 2700 4WD (2008-2012)**ENGINE J2**

Capacity: 7,4 liter (Dry fill), Capacity: 6,4-6,8 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Bi-Turbo 15W-40	Synfleet SHPD 10W-40

Change every 7500 km/ 6 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Bi-Turbo 15W-40	Synfleet SHPD 10W-40

*Change every 4000 km/ 6 months***DIFFERENTIAL FRONT (4x4)**

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 20000 km, change every 40000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

*Change every 10000 km/ 6 months***DIFFERENTIAL REAR (4x4)**

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 20000 km, change every 40000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 10000 km/ 6 months

KIA (EU) K SERIES K 2700 4WD (2008-2012)**DIFFERENTIAL REAR LIMITED SLIP (4x4)**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 20000 km, change every 40000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 10000 km/ 6 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,2-2,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 20000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Change every 100000 km***TRANSFERBOX (4x4)**

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 20000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 20000 km/ 12 months, change every 100000 km*

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

POWER STEERING

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 10000 km/ 6 months

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

COOLING SYSTEM

Capacity: 8,5 liter, Capacity: 9,5 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 10000 km/ 6 months, change every 48000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.