BMC BELDE BELDE 260 SLF EURO 3 (2006 AND AFTER)



ENGINE Cummins ISCe 260-30 (Euro 3 Capacity: 23,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 10000 km/ 3 months/ 250	hours	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 5000 km		·

DIFFERENTIAL REAR Rockwell (N	Meritor) 167E	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Chack avery 10000 km/2 months	change avery 20000 km/ 12 months/ 1000 hours	

Check every 10000 km/ 3 months, change every 30000 km/ 12 months/ 1000 hours

TRANSMISSION AUTOMATIC ZF Capacity: 30 liter (Initial fill)	5HP502C 5/1		
use Normal		climate Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Chaok avan 10000 km/2 months	·		

Check every 10000 km/3 months

OWER STEERING	
SE	CLIMATE
lormal	Moderate
RODUCT RECOMMENDATION 1	
TF Dexron II-D	
ATF Dexron II-D	

BMC BELDE BELDE 260 SLF EURO 3 (2006 AND AFTER)



CENTRAL LUBRICATION SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES GENE	RAL	

COOLING SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.