

## DAF BUS CHASSIS DB 250 RS (TILL 2003)



**ENGINE RS 200**  
Capacity: 26 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth 10W-40</b>	<b>Synfleet SHPD 10W-40</b>	<b>Armado Synth 5W-30</b>

*Change every 20000 km/ 12 months*

**DIFFERENTIAL REAR GKN D66-11B-1G**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

**HUB REDUCTIONS REAR 1354**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

**TRANSMISSION AUTOMATIC Voith D 851.3 3/1**  
Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

**TRANSMISSION AUTOMATIC Voith D 854.3 4/1**  
Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

**TRANSMISSION AUTOMATIC ZF 4/5HP 500 4/1**  
Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**DAF BUS CHASSIS DB 250 RS (TILL 2003)****POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF-A</b>

*Check every 20000 km/ 12 months*

**CENTRAL LUBRICATION SYSTEM** Willy Vogel

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

**WHEEL BEARINGS FRONT** N130

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 20000 km, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*