

DAF LF55 LF 55.250 (4X2) EURO 4/5 (2006-2009)



ENGINE GR 184 S1
Capacity: 19,5 liter

USE	CLIMATE
Normal, fuel sulfur level < 0,2 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 45000 km/ 12 months

USE	CLIMATE
Normal, fuel sulfur level > 0,2 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 22500 km/ 12 months

DIFFERENTIAL REAR HYPOID SR 1026
Capacity: 9 liter

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

Check every 45000 km, change every 100000 km/ 12 months

USE	CLIMATE
Short distance, extended	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 45000 km/ 12 months, change every 120000 km/ 24 months

USE	CLIMATE
Long distance, extended	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 45000 km/ 12 months, change every 300000 km/ 36 months

USE	CLIMATE
Regional, extended	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 45000 km/ 12 months, change every 300000 km/ 36 months

DAF LF55 LF 55.250 (4X2) EURO 4/5 (2006-2009)


DIFFERENTIAL REAR HYPOID SR 1132

Capacity: 9 liter

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

Check every 45000 km, change every 100000 km/ 12 months

USE		CLIMATE
Short distance, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 30000 km/ 12 months, change every 120000 km/ 24 months

USE		CLIMATE
Long distance, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 45000 km/ 12 months, change every 300000 km/ 36 months

USE		CLIMATE
Regional, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 45000 km/ 12 months, change every 300000 km/ 36 months

DAF LF55 LF 55.250 (4X2) EURO 4/5 (2006-2009)



TRANSMISSION AUTOMATED ZF 6AS-1000 (AS-Tronic lite) 6/1
Capacity: 9,3 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1 Syngear MT/LD 75W-80		
---	--	--

Check every 35000 km, change every 100000 km/ 12 months

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1 Syngear MT/LD 75W-80		
---	--	--

Check every 55000 km, change every 150000 km/ 12 months

USE	CLIMATE
Regional	Moderate

PRODUCT RECOMMENDATION 1 Syngear MT/LD 75W-80		
---	--	--

Check every 45000 km, change every 100000 km/ 12 months

TRANSMISSION AUTOMATIC Allison MD 3000 6/1

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1 SP Matic 2032		
--	--	--

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 SP Matic 2032	PRODUCT RECOMMENDATION 2 ATF Almirol	
--	--	--

DAF LF55 LF 55.250 (4X2) EURO 4/5 (2006-2009)



TRANSMISSION MANUAL ZF 6S-1000 6/1

Capacity: 10,5 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80

Check every 35000 km, change every 100000 km/ 12 months

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80

Check every 55000 km, change every 150000 km/ 12 months

USE	CLIMATE
Regional	Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80

Check every 45000 km, change every 100000 km/ 12 months

HYDRAULIC CAB TILT SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

Check every 45000 km/ 12 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

PRODUCT RECOMMENDATION 3

ATF-A

Check every 45000 km/ 12 months

DAF LF55 LF 55.250 (4X2) EURO 4/5 (2006-2009)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

Check every 45000 km/ 12 months

COOLING SYSTEM

Capacity: 22 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 45000 km/ 12 months

WHEEL BEARINGS OIL LUBRICATED

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

Check every 45000 km, change every 100000 km/ 12 months

USE		CLIMATE
Short distance, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 45000 km/ 12 months, change every 120000 km/ 24 months

USE		CLIMATE
Long distance, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 45000 km/ 12 months, change every 300000 km/ 36 months

USE		CLIMATE
Regional, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 45000 km/ 12 months, change every 300000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.