

# DANA SPICER AXLES AXLES, SINGLE DRIVE 16121


**AXLE SINGLE DRIVE Dana 16121**

Capacity: 16 liter (Eaton housing (rectangular arm)), Capacity: 11 liter (Vendor housing (round arm))

| USE                       | CLIMATE  |
|---------------------------|----------|
| Off-Highway use, extended | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |
|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Change every 160000 km/ 12 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Off-Highway use | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3       |
|--------------------------|---------------------------|--------------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Gearlube HS GL-5 75W-90</b> |

*Change every 64000 km/ 12 months*

| USE         | CLIMATE  |
|-------------|----------|
| Highway use | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3       |
|--------------------------|---------------------------|--------------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Gearlube HS GL-5 75W-90</b> |

*Change every 160000 km/ 12 months*

| USE                   | CLIMATE  |
|-----------------------|----------|
| Highway use, extended | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |
|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Change every 400000 km/ 36 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.