

DANA SPICER AXLES AXLES, TANDEM DRIVE DP/RP440-P (TILL 2010)



AXLE TANDEM DRIVE Dana DP/RP440

USE	CLIMATE
Standard, line haul	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 12 months

USE	CLIMATE
Standard, line haul	Arctic

PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Change every 200000 km/ 12 months

USE	CLIMATE
Standard, vocational/bus	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Change every 100000 km/ 12 months

USE	CLIMATE
Standard, vocational/bus	Arctic

PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Change every 100000 km/ 12 months

USE	CLIMATE
Line haul, extended service, axles with LMS wheel bearing system	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 60 months

USE	CLIMATE
Vocational, extended service, axles with adjustable wheel bearing system	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 100000 km/ 12 months

USE	CLIMATE
Vocational, extended service , axles with LMS wheel bearing system	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 12 months

DANA SPICER AXLES AXLES, TANDEM DRIVE DP/RP440-P (TILL 2010)



USE		CLIMATE
Line haul, extended service, axles with adjustable wheel bearing system		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 400000 km/ 36 months</i>		
USE		CLIMATE
Initial service, standard		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90
<i>Change every 8000 km</i>		
USE		CLIMATE
Initial service, standard		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
<i>Change every 8000 km</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.