

DETROIT DIESEL SERIES DD DD13 EPA 10 (2010-2015)

**ENGINE DD13**

Capacity: 36,6 liter, Filter capacity: 1,6 liter

| USE | CLIMATE |
|--------------------|---------------|
| Severe (preferred) | Mediterranean |

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40*Change every 35000 miles/ 6 months/ 750 hours*

| USE | CLIMATE |
|--------------------|----------|
| Severe (preferred) | Moderate |

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30

PRODUCT RECOMMENDATION 2

Armado Synth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet LSP Ultra 10W-30*Change every 35000 miles/ 6 months/ 750 hours*

| USE | CLIMATE |
|---------------------------|---------------|
| Long distance (preferred) | Mediterranean |

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40*Change every 60000 miles/ 12 months*

| USE | CLIMATE |
|---------------------------|----------|
| Long distance (preferred) | Moderate |

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30

PRODUCT RECOMMENDATION 2

Armado Synth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet LSP Ultra 10W-30*Change every 60000 miles/ 12 months*

| USE | CLIMATE |
|---------------------------------------|---------------|
| Light Duty, long distance (preferred) | Mediterranean |

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40*Change every 75000 miles/ 12 months*

| USE | CLIMATE |
|---------------------------------------|----------|
| Light Duty, long distance (preferred) | Moderate |

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30

PRODUCT RECOMMENDATION 2

Armado Synth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet LSP Ultra 10W-30*Change every 75000 miles/ 12 months*

| USE | CLIMATE |
|------------------------|---------------|
| Short haul (preferred) | Mediterranean |

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40*Change every 45000 miles/ 12 months/ 1000 hours*

DETROIT DIESEL SERIES DD DD13 EPA 10 (2010-2015)



| | | |
|-----------------------------------------------------------------|------------------------------------------------------------------|-----------------------------------------------------------------|
| USE Short haul (preferred) | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30 | PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40 | PRODUCT RECOMMENDATION 3 Dieselfleet LSP Ultra 10W-30 |
| <i>Change every 45000 miles/ 12 months/ 1000 hours</i> | | |
| USE Short haul | | CLIMATE Mediterranean |
| PRODUCT RECOMMENDATION 1 Dieselfleet MSP 15W-40 | | |
| <i>Change every 35000 miles/ 895 hours/ 12 months</i> | | |
| USE Short haul | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30 | | |
| <i>Change every 35000 miles/ 895 hours/ 12 months</i> | | |
| USE Alternative, reduced drain intervals | | CLIMATE Mediterranean |
| PRODUCT RECOMMENDATION 1 Dieselfleet MSP 15W-40 | | |
| USE Alternative, reduced drain intervals | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30 | PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40 | PRODUCT RECOMMENDATION 3 Dieselfleet LSP Ultra 10W-30 |
| USE Severe | | CLIMATE Mediterranean |
| PRODUCT RECOMMENDATION 1 Dieselfleet MSP 15W-40 | | |
| <i>Change every 25000 miles/ 640 hours/ 6 months</i> | | |
| USE Severe | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30 | | |
| <i>Change every 25000 miles/ 640 hours/ 6 months</i> | | |

DETROIT DIESEL SERIES DD DD13 EPA 10 (2010-2015)



| USE | | CLIMATE |
|-------------------------------|--|---------------|
| Long distance | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Dieselfleet MSP 15W-40 | | |

Change every 50000 miles/ 12 months/ 1280 hours

| USE | | CLIMATE |
|-------------------------------------|--|----------|
| Long distance | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Armado Synth LSP Ultra 5W-30 | | |

Change every 50000 miles/ 12 months/ 1280 hours

| COOLING SYSTEM | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Check every 20000 miles/ 3 months, change every 600000 miles/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.