

# DETROIT DIESEL SERIES 60 60 (11.1 LITRE) (1988-1998)



**ENGINE** DD60  
Capacity: 37,9 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 6000 miles/ 12 months/ 300 hours*

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 6000 miles/ 12 months/ 300 hours*

USE	CLIMATE
Highway use	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 15000 miles*

USE	CLIMATE
Highway use	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 15000 miles*

## COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>

*Check every 60000 miles/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>

*Check every 12000 miles/ 600 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*