

EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED T-905B



TRANSMISSION Eaton-Fuller 905 5/1
Capacity: 10 liter

| USE | CLIMATE |
|----------------------------------|----------|
| Off Highway use, initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| Multifleet SCD 50 | Multifleet SCD 40 | HDX 50 |

Change every 30 hours

| USE | CLIMATE |
|----------------------------------|---------|
| Off Highway use, initial service | Arctic |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|------------------------------|--------------------------|
| Multifleet SCD 30 | Multifleet SCD 20W-20 | HDX 30 |

Change every 30 hours

| USE | CLIMATE |
|------------------------------|----------|
| Highway use, initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| Multifleet SCD 50 | Multifleet SCD 40 | HDX 50 |

Change every 8000 km

| USE | CLIMATE |
|------------------------------|---------|
| Highway use, initial service | Arctic |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|------------------------------|--------------------------|
| Multifleet SCD 30 | Multifleet SCD 20W-20 | HDX 30 |

Change every 8000 km

| USE | CLIMATE |
|-------------------------|----------|
| Off-Highway use, severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| Multifleet SCD 50 | Multifleet SCD 40 | HDX 50 |

Check every 40 hours, change every 500 hours

| USE | CLIMATE |
|-------------------------|---------|
| Off-Highway use, severe | Arctic |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|------------------------------|--------------------------|
| Multifleet SCD 30 | Multifleet SCD 20W-20 | HDX 30 |

Check every 40 hours, change every 500 hours

| USE | CLIMATE |
|-----------------|----------|
| Off-Highway use | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| Multifleet SCD 50 | Multifleet SCD 40 | HDX 50 |

Check every 40 hours, change every 1000 hours

EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED T-905B



| USE | | CLIMATE |
|--------------------------|------------------------------|--------------------------|
| Off-Highway use | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Multifleet SCD 30 | Multifleet SCD 20W-20 | HDX 30 |

Check every 40 hours, change every 1000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Highway use | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Multifleet SCD 50 | Multifleet SCD 40 | HDX 50 |

Check every 16000 km, change every 80000 km

| USE | | CLIMATE |
|--------------------------|------------------------------|--------------------------|
| Highway use | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Multifleet SCD 30 | Multifleet SCD 20W-20 | HDX 30 |

Check every 16000 km, change every 80000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.