

# EATON FULLER HEAVY-DUTY TRANSMISSIONS 9 SPEED RTO-11109B- ATR



**TRANSMISSION** Eaton-Fuller 11109 9/1  
Capacity: 42 liter

USE	CLIMATE
Off Highway use, initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 10W</b>	<b>Gear Oil Alcat 10W</b>	<b>ATF Dexron II-D</b>

*Change every 30 hours*

USE	CLIMATE
Highway use, initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 10W</b>	<b>Gear Oil Alcat 10W</b>	<b>ATF Dexron II-D</b>

*Change every 2500 km*

USE	CLIMATE
Off-Highway use, severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 10W</b>	<b>Gear Oil Alcat 10W</b>	<b>ATF Dexron II-D</b>

*Check every 40 hours, change every 500 hours*

USE	CLIMATE
Off-Highway use	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 10W</b>	<b>Gear Oil Alcat 10W</b>	<b>ATF Dexron II-D</b>

*Check every 40 hours, change every 1000 hours*

USE	CLIMATE
Highway use	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 10W</b>	<b>Gear Oil Alcat 10W</b>	<b>ATF Dexron II-D</b>

*Check every 4000 km, change every 80000 km/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*