

# EATON FULLER HEAVY-DUTY TRANSMISSIONS 9 SPEED RTXF-12509



**TRANSMISSION** Eaton-Fuller 12509 9  
Capacity: 12 liter

USE	CLIMATE
Off Highway use, initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>HDX 50</b>

*Change every 30 hours*

USE	CLIMATE
Off Highway use, initial service	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 30</b>	<b>Multifleet SCD 20W-20</b>	<b>HDX 30</b>

*Change every 30 hours*

USE	CLIMATE
Off-Highway use, severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>HDX 50</b>

*Check every 40 hours, change every 500 hours*

USE	CLIMATE
Off-Highway use, severe	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 30</b>	<b>Multifleet SCD 20W-20</b>	<b>HDX 30</b>

*Check every 40 hours, change every 500 hours*

USE	CLIMATE
Off-Highway use	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>HDX 50</b>

*Check every 40 hours, change every 1000 hours*

USE	CLIMATE
Off-Highway use	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 30</b>	<b>Multifleet SCD 20W-20</b>	<b>HDX 30</b>

*Check every 40 hours, change every 1000 hours*

USE	CLIMATE
Highway use	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>HDX 50</b>

*Check every 8000 km, change every 80000 km/ 12 months*

# EATON FULLER HEAVY-DUTY TRANSMISSIONS 9 SPEED RTXF-12509



USE		CLIMATE
Highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 30</b>	<b>Multifleet SCD 20W-20</b>	<b>HDX 30</b>
Check every 8000 km, change every 80000 km/ 12 months		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*