PRODUCT RECOMMENDATION

EATON FULLER HEAVY-DUTY TRANSMISSIONS 9 SPEED RTXF-12609P

TRANSMISSION Eaton-Fuller 12609 9
Capacity: 13 liter

USE		CLIMATE
Off Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**HDX 50**
Change every 30 hours		

USE		CLIMATE
Off Highway use, initial service		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 30	**Multifleet SCD 20W-20**	**HDX 30**
Change every 30 hours		

USE		CLIMATE
Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**HDX 50**
Change every 8000 km		

USE		CLIMATE
Highway use, initial service		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 30	**Multifleet SCD 20W-20**	**HDX 30**
Change every 8000 km		

USE		CLIMATE
Off-Highway use, severe		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**HDX 50**
Check every 40 hours, change every 500 hours		

USE		CLIMATE
Off-Highway use, severe		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 30	**Multifleet SCD 20W-20**	**HDX 30**
Check every 40 hours, change every 500 hours		

USE		CLIMATE
Off-Highway use		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**HDX 50**
Check every 40 hours, change every 1000 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

EATON FULLER HEAVY-DUTY TRANSMISSIONS 9 SPEED RTXF-12609P

USE		CLIMATE
Off-Highway use		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 30	**Multifleet SCD 20W-20**	**HDX 30**
Check every 40 hours, change every 1000 hours		

USE		CLIMATE
Highway use		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**HDX 50**
Check every 16000 km, change every 80000 km		

USE		CLIMATE
Highway use		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 30	**Multifleet SCD 20W-20**	**HDX 30**
Check every 16000 km, change every 80000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367