EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FR-14210B



| apacity: 11 liter | | |
|------------------------------------|--------------------------|------------------------------------|
| JSE | | CLIMATE |
| Standard, line haul | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Multifleet SCD 50 | Multifleet SCD 40 | Gearlube GL-4 80W-90 |
| Change every 100000 km | | |
| USE | | CLIMATE |
| Standard, line haul | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |
| Change every 100000 km | | |
| USE | | CLIMATE |
| Standard, vocational/bus | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Multifleet SCD 50 | Multifleet SCD 40 | Gearlube GL-4 80W-90 |
| Change every 100000 km/ 12 months | | |
| USE | | CLIMATE |
| Standard, vocational/bus | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |
| Change every 100000 km/ 12 months | | |
| USE | | CLIMATE |
| Standard, stationary | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Multifleet SCD 50 | Multifleet SCD 40 | Gearlube GL-4 80W-90 |
| Change every 500 hours/ 12 months | | · |
| JSE | | CLIMATE |
| Standard, stationary | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |
| Change every 500 hours/ 12 months | | ' |
| sharige every 500 hours/ 12 months | | CLIMATE |
| USE | | |
| | | Moderate |
| USE | PRODUCT RECOMMENDATION 2 | Moderate PRODUCT RECOMMENDATION 3 |

EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FR-14210B



| USE | | CLIMATE |
|---|--------------------------|--------------------------|
| Standard, initial service, stationary | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |
| Change every 2 months/ 40 hours | | |
| USE | | CLIMATE |
| Standard, initial service, on highway use | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Multifleet SCD 50 | Multifleet SCD 40 | Gearlube GL-4 80W-90 |
| Change every 8000 km | | |
| USE | | CLIMATE |
| Standard, initial service, on highway use | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |
| Change every 8000 km | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.