## **EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FRO-13210B**



Capacity: 11 liter		
JSE		CLIMATE
Standard, line haul		Moderate
PRODUCT RECOMMENDATION 1  Multifleet SCD 50	PRODUCT RECOMMENDATION 2  Multifleet SCD 40	PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90
	Multifleet SCD 40	Geanube GL-4 80W-90
Change every 100000 km		
JSE		CLIMATE
Standard, line haul		Arctic
PRODUCT RECOMMENDATION 1  Multifleet SCD 30	Gear Oil Alcat 30	
	Geal Oil Alcat 30	
Change every 100000 km		
USE Standard vacational/bus		CLIMATE
Standard, vocational/bus		Moderate
PRODUCT RECOMMENDATION 1  Multifleet SCD 50	PRODUCT RECOMMENDATION 2  Multifleet SCD 40	PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90
	Multifleet SCD 40	Geanupe GL-4 80W-90
Change every 100000 km/ 12 months		
USE		CLIMATE
Standard, vocational/bus		Arctic
PRODUCT RECOMMENDATION 1  Multifleet SCD 30	Gear Oil Alcat 30	
	Geal Oil Alcat 30	
Change every 100000 km/ 12 months		
JSE		CLIMATE
use Standard, stationary		Moderate
USE Standard, stationary PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Moderate  PRODUCT RECOMMENDATION 3
USE Standard, stationary PRODUCT RECOMMENDATION 1 Multifleet SCD 50	PRODUCT RECOMMENDATION 2  Multifleet SCD 40	Moderate
Standard, stationary PRODUCT RECOMMENDATION 1 Multifleet SCD 50 Change every 500 hours/ 12 months		Moderate  PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90
Standard, stationary PRODUCT RECOMMENDATION 1  Multifleet SCD 50  Change every 500 hours/ 12 months  USE		Moderate  PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90  CLIMATE
Standard, stationary PRODUCT RECOMMENDATION 1  Multifleet SCD 50  Change every 500 hours/ 12 months  USE  Standard, stationary	Multifleet SCD 40	Moderate  PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90
Standard, stationary  PRODUCT RECOMMENDATION 1  Multifleet SCD 50  Change every 500 hours/ 12 months  USE  Standard, stationary  PRODUCT RECOMMENDATION 1	Multifleet SCD 40  PRODUCT RECOMMENDATION 2	Moderate  PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90  CLIMATE
Standard, stationary PRODUCT RECOMMENDATION 1  Multifleet SCD 50  Change every 500 hours/ 12 months  USE  Standard, stationary PRODUCT RECOMMENDATION 1  Multifleet SCD 30	Multifleet SCD 40	Moderate  PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90  CLIMATE
Standard, stationary PRODUCT RECOMMENDATION 1  Multifleet SCD 50  Change every 500 hours/ 12 months  USE  Standard, stationary PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 500 hours/ 12 months	Multifleet SCD 40  PRODUCT RECOMMENDATION 2	Moderate  PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90  CLIMATE  Arctic
Standard, stationary PRODUCT RECOMMENDATION 1  Multifleet SCD 50  Change every 500 hours/ 12 months  USE  Standard, stationary PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 500 hours/ 12 months	Multifleet SCD 40  PRODUCT RECOMMENDATION 2  Gear Oil Alcat 30	Moderate  PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90  CLIMATE  Arctic
Standard, stationary  PRODUCT RECOMMENDATION 1  Multifleet SCD 50  Change every 500 hours/ 12 months  USE  Standard, stationary  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 500 hours/ 12 months  USE  Standard, initial service, stationary  PRODUCT RECOMMENDATION 1	Multifleet SCD 40  PRODUCT RECOMMENDATION 2  Gear Oil Alcat 30	Moderate  PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90  CLIMATE  Arctic

## EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FRO-13210B



USE		CLIMATE
Standard, initial service, stationary		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 2 months/ 40 hours		
USE		CLIMATE
Standard, initial service, on highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 8000 km		
USE		CLIMATE
Standard, initial service, on highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 8000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.