

EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FROF-12210C



TRANSMISSION Eaton-Fuller 11210 10
Capacity: 11 liter

USE	CLIMATE
Standard, line haul	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

Change every 100000 km

USE	CLIMATE
Standard, line haul	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Gear Oil Alcat 30	

Change every 100000 km

USE	CLIMATE
Standard, vocational/bus	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

Change every 100000 km/ 12 months

USE	CLIMATE
Standard, vocational/bus	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Gear Oil Alcat 30	

Change every 100000 km/ 12 months

USE	CLIMATE
Standard, stationary	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

Change every 500 hours/ 12 months

USE	CLIMATE
Standard, stationary	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Gear Oil Alcat 30	

Change every 500 hours/ 12 months

USE	CLIMATE
Standard, initial service, stationary	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

Change every 2 months/ 40 hours

EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FROF-12210C



USE		CLIMATE
Standard, initial service, stationary		Arctic
PRODUCT RECOMMENDATION 1 Multifleet SCD 30	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30	
<i>Change every 2 months/ 40 hours</i>		
USE		CLIMATE
Standard, initial service, on highway use		Moderate
PRODUCT RECOMMENDATION 1 Multifleet SCD 50	PRODUCT RECOMMENDATION 2 Multifleet SCD 40	PRODUCT RECOMMENDATION 3 Gearlube GL-4 80W-90
<i>Change every 8000 km</i>		
USE		CLIMATE
Standard, initial service, on highway use		Arctic
PRODUCT RECOMMENDATION 1 Multifleet SCD 30	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30	
<i>Change every 8000 km</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.