PRODUCT RECOMMENDATION

EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FROF-14210B

TRANSMISSION Eaton-Fuller 14210 10
Capacity: 11 liter

USE		CLIMATE
Standard, line haul		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**Gearlube GL-4 80W-90**
Change every 100000 km		

USE		CLIMATE
Standard, line haul		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 30	**Gear Oil Alcat 30**	
Change every 100000 km		

USE		CLIMATE
Standard, vocational/bus		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**Gearlube GL-4 80W-90**
Change every 100000 km/ 12 months		

USE		CLIMATE
Standard, vocational/bus		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 30	**Gear Oil Alcat 30**	
Change every 100000 km/ 12 months		

USE		CLIMATE
Standard, stationary		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**Gearlube GL-4 80W-90**
Change every 500 hours/ 12 months		

USE		CLIMATE
Standard, stationary		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 30	**Gear Oil Alcat 30**	
Change every 500 hours/ 12 months		

USE		CLIMATE
Standard, initial service, stationary		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**Gearlube GL-4 80W-90**
Change every 2 months/ 40 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FROF-14210B

USE		CLIMATE
Standard, initial service, stationary		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 30	**Gear Oil Alcat 30**	
Change every 2 months/ 40 hours		

USE		CLIMATE
Standard, initial service, on highway use		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SCD 50	**Multifleet SCD 40**	**Gearlube GL-4 80W-90**
Change every 8000 km		

USE		CLIMATE
Standard, initial service, on highway use		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 30	**Gear Oil Alcat 30**	
Change every 8000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367