

# EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED RTXF-13710C



**TRANSMISSION** Eaton-Fuller 13710 10  
Capacity: 12 liter

USE	CLIMATE
Off Highway use, initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>Gearlube GL-4 80W-90</b>

*Change every 2 months/ 40 hours*

USE	CLIMATE
Off Highway use, initial service	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 30</b>	<b>Gear Oil Alcat 30</b>	

*Change every 2 months/ 40 hours*

USE	CLIMATE
Highway use, initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>Gearlube GL-4 80W-90</b>

*Change every 8000 km*

USE	CLIMATE
Highway use, initial service	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 30</b>	<b>Gear Oil Alcat 30</b>	

*Change every 8000 km*

USE	CLIMATE
Standard, line haul	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>Gearlube GL-4 80W-90</b>

*Change every 100000 km*

USE	CLIMATE
Standard, line haul	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 30</b>	<b>Gear Oil Alcat 30</b>	

*Change every 100000 km*

USE	CLIMATE
Standard, vocational/bus	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>Gearlube GL-4 80W-90</b>

*Change every 100000 km/ 12 months*

# EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED RTXF-13710C



USE		CLIMATE
Standard, vocational/bus		Arctic
PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 30</b>	PRODUCT RECOMMENDATION 2 <b>Gear Oil Alcat 30</b>	
<i>Change every 100000 km/ 12 months</i>		
USE		CLIMATE
Standard, stationary		Moderate
PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 50</b>	PRODUCT RECOMMENDATION 2 <b>Multifleet SCD 40</b>	PRODUCT RECOMMENDATION 3 <b>Gearlube GL-4 80W-90</b>
<i>Change every 500 hours/ 12 months</i>		
USE		CLIMATE
Standard, stationary		Arctic
PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 30</b>	PRODUCT RECOMMENDATION 2 <b>Gear Oil Alcat 30</b>	
<i>Change every 500 hours/ 12 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.