

EATON FULLER HEAVY-DUTY TRANSMISSIONS 13 -> 18 SPEED RT-14615



TRANSMISSION Eaton-Fuller 14615 15
Capacity: 14,2 liter

USE	CLIMATE	
Off Highway use, initial service	Moderate	

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	HDX 50

Change every 30 hours

USE	CLIMATE	
Off Highway use, initial service	Arctic	

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30

Change every 30 hours

USE	CLIMATE	
Highway use, initial service	Moderate	

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	HDX 50

Change every 8000 km

USE	CLIMATE	
Highway use, initial service	Arctic	

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30

Change every 8000 km

USE	CLIMATE	
Off-Highway use, severe	Moderate	

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	HDX 50

Check every 40 hours, change every 500 hours

USE	CLIMATE	
Off-Highway use, severe	Arctic	

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30

Check every 40 hours, change every 500 hours

USE	CLIMATE	
Off-Highway use	Moderate	

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	HDX 50

Check every 40 hours, change every 1000 hours

EATON FULLER HEAVY-DUTY TRANSMISSIONS 13 -> 18 SPEED RT-14615



USE		CLIMATE
Off-Highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30

Check every 40 hours, change every 1000 hours

USE		CLIMATE
Highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	HDX 50

Check every 16000 km, change every 80000 km

USE		CLIMATE
Highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Multifleet SCD 20W-20	HDX 30

Check every 16000 km, change every 80000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.