

ERF EC11 EC11.34 (6X4/8X4) (1995-2002)

ENGINE Cummins M340E Celect
Capacity: 42 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 20000 km

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet LSP Ultra 10W-30	Multifleet SHPD 10W-40

Change every 20000 km

DIFFERENTIAL REAR LEADING Rockwell RT52-153
Capacity: 20,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 16000 km, change every 200000 km/ 12 months

DIFFERENTIAL REAR TRAILING Rockwell RT52-153
Capacity: 16,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 16000 km, change every 200000 km/ 12 months

TRANSMISSION MANUAL Eaton RTX 14609 A 9/2
Capacity: 12,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 16000 km, change every 100000 km/ 6 months

ERF EC11 EC11.34 (6X4/8X4) (1995-2002)**TRANSMISSION MANUAL** Eaton TSO 12612A (Twin Splitter) 12/2

Capacity: 15 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 16000 km, change every 100000 km/ 6 months***TRANSMISSION MANUAL SYNCHROMESH** Eaton RTSO 12316 A 16/2

Capacity: 12,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Check every 16000 km, change every 100000 km/ 6 months***TRANSMISSION MANUAL SYNCHROMESH** ZF 8S-151 8/2

Capacity: 9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Check every 16000 km, change every 100000 km/ 6 months***HYDRAULIC CAB TILT SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 16000 km***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 16000 km, change every 200000 km/ 12 months*

ERF EC11 EC11.34 (6X4/8X4) (1995-2002)**POWER STEERING**

Capacity: 4,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D***Check every 16000 km***CENTRAL LUBRICATION SYSTEM Tecalemit XGS****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 16000 km***CENTRAL LUBRICATION SYSTEM GREASE Tecalemit XGS****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gear Grease EP 00/000***Check every 16000 km***GREASE POINTS/NIPPLES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**MoS2 Grease EP 2***Check every 16000 km***GREASE POINTS/NIPPLES OTHERS****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Check every 16000 km*

ERF EC11 EC11.34 (6X4/8X4) (1995-2002)**COOLING SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 16000 km, change every 200000 km/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.