PRODUCT RECOMMENDATION

# ERF ES8 ES 8.30 (6X4) (1996-2002)

## ENGINE Cummins C300
Capacity: 23,6 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SHPD 15W-40** | | |

*Change every 25000 km/ 6 months*

## DIFFERENTIAL REAR LEADING Rockwell RT52-153
Capacity: 20,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 16000 km, change every 200000 km/ 12 months*

## DIFFERENTIAL REAR TRAILING Rockwell RT52-153
Capacity: 16,6 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 16000 km, change every 200000 km/ 12 months*

## TRANSMISSION AUTOMATIC Allison MD 3560P 5/1
Capacity: 27 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gear Oil Alcat 10W** | **ATF Dexron II-D** | |

## TRANSMISSION MANUAL Eaton FS-8209A 9/1
Capacity: 8,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Gear 5015** | **Gearlube GL-4 80W** | |

*Check every 16000 km, change every 100000 km/ 6 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# ERF ES8 ES 8.30 (6X4) (1996-2002)

## TRANSMISSION MANUAL Eaton RTX 11609 A 9/1
Capacity: 13 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 16000 km, change every 100000 km/ 6 months*

## TRANSMISSION MANUAL Eaton ZF 9S-109 9/1
Capacity: 8,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **SP Gear 5015** | **Gearlube GL-4 80W** | |

*Check every 16000 km, change every 100000 km/ 6 months*

## HYDRAULIC CAB TILT SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **ATF Dexron II-D** | | |

*Check every 16000 km*

## HYDRAULIC CLUTCH SYSTEM
Capacity: 0,7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Drauliquid DOT 3** | | |

*Check every 16000 km, change every 200000 km/ 12 months*

## POWER STEERING
Capacity: 4,7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **ATF Dexron II-D** | | |

*Check every 16000 km*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# ERF ES8 ES 8.30 (6X4) (1996-2002)

## GREASE POINTS/NIPPLES OTHERS

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

## GREASE POINTS/NIPPLES TRAILER COUPLING

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **MoS2 Grease EP 2** | | |
| *Check every 16000 km* | | |

## COOLING SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Coolant -38 Organic NF** | **Coolant -26** | |
| *Check every 16000 km, change every 200000 km/ 12 months* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367