

FORD (USA) F-550 (SUPER DUTY) F-550 6.7 TD SUPER DUTY 4X4 (2011-2016)



ENGINE Power Stroke
Capacity: 12,4 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth MSP 5W-40

Change every 5000 miles/ 6 months

USE	CLIMATE
Flexible (max)	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Change every 10000 miles/ 12 months

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth MSP 5W-40

PRODUCT RECOMMENDATION 2

Dieselfleet MSP 10W-30

Change every 10000 miles/ 12 months

USE	CLIMATE
Biodiesel B6-B20	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Change every 15000 miles/ 6 months/ 600 hours

USE	CLIMATE
Biodiesel B6-B20	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth MSP 5W-40

Change every 15000 miles/ 6 months/ 600 hours

USE	CLIMATE
Normal, fuel sulfur level > 500 ppm	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Change every 2500 miles/ 3 months

USE	CLIMATE
Normal, fuel sulfur level > 500 ppm	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth MSP 5W-40

PRODUCT RECOMMENDATION 2

Dieselfleet MSP 10W-30

Change every 2500 miles/ 3 months

FORD (USA) F-550 (SUPER DUTY) F-550 6.7 TD SUPER DUTY 4X4 (2011-2016)



USE		CLIMATE
Normal, fuel sulfur level 15-500 ppm		Mediterranean
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		

Change every 5000 miles/ 6 months

USE		CLIMATE
Normal, fuel sulfur level 15-500 ppm		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth MSP 5W-40	Dieselfleet MSP 10W-30	

Change every 5000 miles/ 6 months

DIFFERENTIAL FRONT (4x4) Capacity: 2,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 150000 miles

DIFFERENTIAL REAR Dana S110/S130 Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 105000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 50000 miles



FORD (USA) F-550 (SUPER DUTY) F-550 6.7 TD SUPER DUTY 4X4 (2011-2016)

**TRANSFERBOX**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Change every 150000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Change every 60000 miles***TRANSMISSION AUTOMATIC 5R110W 5/1**

Capacity: 16,6 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

PRODUCT RECOMMENDATION 2

SP Matic 2032*Change every 60000 miles***TRANSMISSION AUTOMATIC 6R140(W) 6/1**

Capacity: 15,8-17,5 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

PRODUCT RECOMMENDATION 2

SP Matic 2032*Change every 150000 miles***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

FORD (USA) F-550 (SUPER DUTY) F-550 6.7 TD SUPER DUTY 4X4 (2011-2016)



POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

COOLING SYSTEM PRIMARY

Capacity: 27,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months, change every 50000 miles/ 36 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months, change every 100000 miles/ 72 months

COOLING SYSTEM SECONDARY

Capacity: 11,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months, change every 50000 miles/ 36 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months, change every 100000 miles/ 72 months

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

Capacity: 22,7 liter (Cabin/Chassis model), Capacity: 18,9 liter (Pick-up model)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.