FORD (USA) F-550 (SUPER DUTY) F-550 6.8 V10 SUPER DUTY (2011-2016)



ENGINE Triton Capacity: 6,6 liter		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Change every 5000 miles/ 6 months		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Check even, 1 months, change even, 750	miles/6 months	

Check every 1 months, change every 7500 miles/ 6 months

DIFFERENTIAL REAR Dana S110/S130 Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 105000 miles	

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 50000 miles	

TRANSMISSION AUTOMATIC 5R110W 5/1 Capacity: 16,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

Change every 60000 miles

FORD (USA) F-550 (SUPER DUTY) F-550 6.8 V10 SUPER DUTY (2011-2016)



TRANSMISSION AUTOMATIC 6R140(W)6/1Capacity:15,8-17,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

Change every 150000 miles

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
use Normal		climate Moderate
		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

COOLING SYSTEM Capacity: 25,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 6 months, change eve	ery 45000 miles/ 36 months	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Check every 6 months, change every	105000 miles/ 72 months	
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.