

# GKN GKN-KIRKSTALL KIRKSTALL (1988-1995)



## AXLE WORM DRIVE

| USE                          |  | CLIMATE |
|------------------------------|--|---------|
| Normal                       |  | Cold    |
| PRODUCT RECOMMENDATION 1     |  |         |
| <b>Gearlube GL-1 80W-90</b>  |  |         |
| <i>Change every 4 months</i> |  |         |

## DIFFERENTIAL HYPOID

| USE                                    |                                     | CLIMATE  |
|----------------------------------------|-------------------------------------|----------|
| Normal                                 |                                     | Tropical |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube GL-5 85W-140</b>           | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |
| <i>Change every 40000 km/ 6 months</i> |                                     |          |

| USE                                    |                                    | CLIMATE  |
|----------------------------------------|------------------------------------|----------|
| Normal                                 |                                    | Moderate |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b>            | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |
| <i>Change every 40000 km/ 6 months</i> |                                    |          |

| USE                                    |                          | CLIMATE |
|----------------------------------------|--------------------------|---------|
| Normal                                 |                          | Arctic  |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 |         |
| <b>SP Gear 5015</b>                    | <b>SP Gear 1071</b>      |         |
| <i>Change every 40000 km/ 6 months</i> |                          |         |

# GKN GKN-KIRKSTALL KIRKSTALL (1988-1995)



## DIFFERENTIAL SPIRAL BEVEL

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |
|------------------------------|-------------------------------------|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |

Change every 40000 km/ 6 months

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Change every 40000 km/ 6 months

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| <b>SP Gear 5015</b>      | <b>SP Gear 1071</b>      |

Change every 40000 km/ 6 months

## DIFFERENTIAL SPUR REDUCTION

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |
|------------------------------|-------------------------------------|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |

Change every 40000 km/ 6 months

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Change every 40000 km/ 6 months

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| <b>SP Gear 5015</b>      | <b>SP Gear 1071</b>      |

Change every 40000 km/ 6 months

# GKN GKN-KIRKSTALL KIRKSTALL (1988-1995)



## HUB REDUCTIONS REAR

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |
|------------------------------|-------------------------------------|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |

*Change every 40000 km/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

*Change every 40000 km/ 6 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| <b>SP Gear 5015</b>      | <b>SP Gear 1071</b>      |

*Change every 40000 km/ 6 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*