

# IRISBUS EUROPOLIS EUROPOLIS ELECTRIC (2007-2008)



## DIFFERENTIAL REAR

Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140***Change every 40000 km*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 40000 km*

## GEAR CASE TRACTION MOTOR

Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 20000 km*

## HYDRAULIC SYSTEM POWER STEERING + HYDROSTATIC TRANSMISSION

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

## HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

## CENTRAL LUBRICATION SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

# IRISBUS EUROPOLIS EUROPOLIS ELECTRIC (2007-2008)



## WHEEL BEARINGS GREASED

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Labora Grease</b>	<b>Multi Purpose Grease 3</b>	

## COOLING SYSTEM

Capacity: 40 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 11</b>		

## ELECTRIC COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*