## ISUZU F SERIES EURO 4/5 F150.260 EURO **4/5** (2009 AND AFTER)



ENGINE 6HK1 Capacity: 16 liter (deep sump), Capacity: 1	1 liter (shallow sump)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	

S73	
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Unigear HS GL-3/GL-5 80W-90	
	PRODUCT RECOMMENDATION 2

DIFFERENTIAL REAR Meritor RS2	25-160	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

TRANSMISSION AUTOMATIC Easy	Shift 6/1		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

TRANSMISSION MANUAL Eaton	FSO-5206B 6/1	
use Normal		climate Moderate
SP Gear 5015	Gearlube GL-4 80W	Gearlube GL-4 80W-90

HYDRAULIC BRAKE/CLUTCH SYSTEM		
CLIMATE		
Moderate		

Dollegoorweg 15

7602 EC Almelo

## **ISUZU F SERIES EURO 4/5 F150.260 EURO 4/5** (2009 AND AFTER)



POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

COOLING SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.