

IVECO M SERIES M-RANGE 175.17 (1988-1992)

**ENGINE** 8060.25

Capacity: 12,2 liter, Filter capacity: 1,1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 40	Multifleet SCD 30

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Multifleet SCD 20W-20	

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

DIFFERENTIAL REAR (4x2) Rockwell S160E

Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

TRANSMISSION MANUAL ZF S6-36 + GV 12/2

Capacity: 11,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear MT/LD 75W-80	Gearlube GL-4 80W-90

IVECO M SERIES M-RANGE 175.17 (1988-1992)



TRANSMISSION MANUAL ZF S6-36 6/1

Capacity: 9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear MT/LD 75W-80	Gearlube GL-4 80W-90

HYDRAULIC CAB TILT SYSTEM

Capacity: 0,35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING ZF 8043 / HDS 450 Riva e Calzoni

Capacity: 3,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 22 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.