

# MACK MACK ACET ENGINES AI/AC/AMI AI-350 ASET (2002-2007)

**ENGINE** AI-350 ASET

Capacity: 38 liter, Capacity: 30 liter (AWD)

USE	CLIMATE
Severe	Moderate

## PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40***Change every 8000 km/ 45 days/ 150 hours*

USE	CLIMATE
Severe	Arctic

## PRODUCT RECOMMENDATION 1

**Armado Synth LSP 10W-40**

## PRODUCT RECOMMENDATION 2

**Armado Synth 10W-40**

## PRODUCT RECOMMENDATION 3

**Synfleet SHPD 10W-40***Change every 8000 km/ 45 days/ 150 hours*

USE	CLIMATE
Long distance	Moderate

## PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40***Change every 40000 km/ 600 hours*

USE	CLIMATE
Long distance	Arctic

## PRODUCT RECOMMENDATION 1

**Armado Synth LSP 10W-40**

## PRODUCT RECOMMENDATION 2

**Armado Synth 10W-40**

## PRODUCT RECOMMENDATION 3

**Synfleet SHPD 10W-40***Change every 40000 km/ 600 hours*

USE	CLIMATE
Extremely severe	Moderate

## PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40***Change every 6000 km/ 45 days/ 125 hours*

USE	CLIMATE
Extremely severe	Arctic

## PRODUCT RECOMMENDATION 1

**Armado Synth LSP 10W-40**

## PRODUCT RECOMMENDATION 2

**Armado Synth 10W-40**

## PRODUCT RECOMMENDATION 3

**Synfleet SHPD 10W-40***Change every 6000 km/ 45 days/ 125 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.