

MAN LE-C LE-C 10.150 BB/BL (2004-2006)

ENGINE D 0834 LFL04/Euro 3
Capacity: 16,5 liter

USE	CLIMATE
Long distance, green dipstick ring	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 60000 km/ 12 months

USE	CLIMATE
Long distance, red dipstick ring	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 45000 km/ 12 months

USE	CLIMATE
Short distance, green dipstick ring	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 45000 km/ 12 months

USE	CLIMATE
Short distance, red dipstick ring	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 30000 km/ 12 months

DIFFERENTIAL REAR HY-0720
Capacity: 5,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 320000 km/ 36 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 180000 km/ 36 months

MAN LE-C LE-C 10.150 BB/BL (2004-2006)**TRANSMISSION MANUAL ZF S5-42 5/1**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Syngear MT/LD 75W-80		
---	--	--

Change every 320000 km/ 36 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 SP Gear 5015	PRODUCT RECOMMENDATION 3 Syngear MT/LD 75W-80
---	---	---

Change every 180000 km/ 36 months

HYDRAULIC CAB TILT SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Perlus H 15		
--	--	--

Check every 60000 km/ 12 months

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Drauliquid DOT 5.1		
---	--	--

Check every 60000 km/ 12 months

POWER STEERING ZF 8095

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 SP Matic 2032	PRODUCT RECOMMENDATION 2 ATF Almirol	PRODUCT RECOMMENDATION 3 ATF Dexron II-D
--	--	--

Check every 60000 km/ 12 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1 SP Matic 2032	PRODUCT RECOMMENDATION 2 ATF Almirol	PRODUCT RECOMMENDATION 3 ATF Dexron II-D
--	--	--

Check every 60000 km/ 12 months

MAN LE-C LE-C 10.150 BB/BL (2004-2006)**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 500000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.