

MAN TGA TGA 25.350 LL-U (6X2-2) (2004-2008)



ENGINE D 2066 LF03
Capacity: 42 liter

| USE | CLIMATE |
|--------|----------|
| Euro 4 | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------------|--------------------------------------|--------------------------------|
| Armado Synth LSP Ultra 5W-30 | Armado Synth LSP Ultra 10W-40 | Armado Synth LSP 10W-40 |

Change every 120000 km

| USE | CLIMATE |
|----------------|----------|
| Flexible (max) | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|----------------------------|--|--|
| Armado Synth 10W-40 | | |

Change every 120000 km

DIFFERENTIAL REAR HY-1350
Capacity: 14,5 liter

| USE | CLIMATE |
|---------------|----------|
| Long distance | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|-----------------------------|
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube GL-5 80W-90 |

Change every 90000 km/ 36 months

| USE | CLIMATE |
|----------------|----------|
| Short distance | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|-----------------------------|
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube GL-5 80W-90 |

Change every 60000 km/ 36 months

TRANSMISSION MANUAL ZF 16S-192 DD 16/2
Capacity: 13 liter

| USE | CLIMATE |
|---------------|----------|
| Long distance | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-----------------------------|--|--|
| Syngear MT/LD 75W-80 | | |

Change every 90000 km/ 36 months

| USE | CLIMATE |
|----------------|----------|
| Short distance | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-----------------------------|--|--|
| Syngear MT/LD 75W-80 | | |

Change every 60000 km/ 36 months

MAN TGA TGA 25.350 LL-U (6X2-2) (2004-2008)



HYDRAULIC CAB TILT SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 15 | | |

HYDRAULIC CLUTCH + HGS (KONGSBERG) GEAR ACTUATION SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Fluid 3013 | | |

HYDRAULIC CLUTCH SYSTEM

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 5.1 | | |

POWER STEERING

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Alternative (acceptable) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |

CENTRAL LUBRICATION SYSTEM GREASE Vogel

| USE | | CLIMATE |
|------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Grease EP 00/000 | | |

MAN TGA TGA 25.350 LL-U (6X2-2) (2004-2008)**CENTRAL LUBRICATION SYSTEM OIL** Vogel

| USE | | CLIMATE |
|----------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Armado Synth 10W-40 | Armado Synth 5W-30 | |

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| HT Q9 High Grade Grease | | |

COOLING SYSTEM

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Change every 500000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.