
MAN TGA TGA 26.463 FNLC/FNLLC (6X2)





ENGINE 463 (MAN D2876 LF04/EDC Euro 3) Capacity: 43 liter		
USE CLIMATE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40 Armado Synth LSP 10W-40 Armado Synth 10W-40		Armado Synth 10W-40

Change every 6 months

DIFFERENTIAL REAR HY-1350 Capacity: 14,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90
Check every 12 months		

POWER TAKE OFF ZF NMV 221 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear MT/LD 75W-80	Syngear TDL 75W-90
Change every 12 months		

TRANSMISSION MANUAL ZF 16: Capacity: 8 liter	S-221 16/2	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear MT/LD 75W-80	Syngear TDL 75W-90
Change every 6 months	1	

TRANSMISSION MANUAL + INTARDER ZF 16S-221 16/2 Capacity: 11 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
Change every 6 months		

MAN TGA TGA 26.463 FNLC/FNLLC (6X2)



(2000-2002)

HYDRAULIC CAB TILT SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

POWER STEERING Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

CENTRAL LUBRICATION SYSTEM BEKA, Helios, Delimon		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

MAN TGA TGA 26.463 FNLC/FNLLC (6X2) (2000-2002)



GREASE POINTS/NIPPLES FIFTH WHEEL

USE

Normal

Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 00/000

Change every 6 months

GREASE POINTS/NIPPLES HUB UNIT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 50 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 500000 km/ 48 month	is	

SWIVEL PIN HOUSINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Labora Grease		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.