

MAN TGA TGA 32.363 FFDK (8X4) (2001-2004)


ENGINE D 2866 LF27/EDC/Euro 3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Check every 6 months

DIFFERENTIAL REAR LEADING MAN HD 9-13120

Capacity: 16 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Check every 6 months

DIFFERENTIAL REAR TRAILING MAN H 9-13120

Capacity: 13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Check every 6 months

HUB REDUCTIONS REAR MAN H 9-13120

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Check every 6 months

HUB REDUCTIONS REAR MAN HD 9-13120

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Check every 6 months

MAN TGA TGA 32.363 FFDK (8X4) (2001-2004)



TRANSMISSION MANUAL ZF 16S-151 OD 16/2

Capacity: 9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear MT/LD 75W-80	Syngear TDL 75W-90

Check every 6 months

TRANSMISSION MANUAL + INTARDER ZF 16S-151 OD 16/2

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Check every 6 months

HYDRAULIC CAB TILT SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

Check every 6 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 6 months

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 6 months

MAN TGA TGA 32.363 FFDK (8X4) (2001-2004)



CENTRAL LUBRICATION SYSTEM BEKA-MAX, Lincoln, Delimon

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 6 months, change every 48 months

CENTRAL LUBRICATION SYSTEM Groeneveld

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Grease EP 0	Gear Grease EP 00/000	

Check every 6 months, change every 48 months

CENTRAL LUBRICATION SYSTEM GREASE Vogel

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 00/000		

Check every 6 months, change every 48 months

CENTRAL LUBRICATION SYSTEM OIL Vogel

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth 10W-40	Armado Synth 5W-30	

Check every 6 months, change every 48 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 6 months

MAN TGA TGA 32.363 FFDK (8X4) (2001-2004)



GREASE POINTS/NIPPLES PROPELLER SHAFT JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 6 months

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 6 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.