MAZ 6430 6430 B9 (6X4) EURO 4 (2012 AND AFTER)



| ENGINE YaMZ-651 Euro 4 Capacity: 36,4 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Armado Synth LSP Ultra 5W-30 | Armado Synth LSP 10W-40 | Armado Synth 10W-40 |

| DIFFERENTIAL REAR LEADING Capacity: 15-17 liter, Capacity: 2 liter (each hub) | | | |
|---|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube HS GL-5 75W-90 | |

| DIFFERENTIAL REAR TRAILING Capacity: 15-17 liter, Capacity: 2 liter (each hub) | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube HS GL-5 75W-90 |

| TRANSMISSION MANUAL 12JS20 Capacity: 15,5 liter | 00TA 12/2 | |
|--|------------------------------|----------|
| USE | | CLIMATE |
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| SP Gear 5015 | | |

MAZ 6430 6430 B9 (6X4) EURO 4 (2012 AND AFTER)



| TRANSMISSION MANUAL ZF 16S-2520 16/2 | | | |
|--------------------------------------|----------|--|--|
| USE | CLIMATE | | |
| Normal | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| Syngear MT/LD 75W-80 | | | |

| HYDRAULIC CAB TILT SYSTEM Capacity: 0,9 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Fluid 3013 | |

| HYDRAULIC CLUTCH SYSTEM Capacity: 0,5 liter | | | |
|---|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |

| POWER STEERING Capacity: 6,5 liter | | |
|------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |

| GREASE POINTS/NIPPLES BOGIE SUPPORT BEARING Capacity: 0,4 liter (each side) | | | |
|---|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube HS GL-5 75W-90 | |

PRODUCT RECOMMENDATION

MAZ 6430 6430 B9 (6X4) EURO 4 (2012 AND AFTER)



| COOLING SYSTEM Capacity: 36 liter | |
|-----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 16 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.