

ENGINE OM502LA II/2(542.921) Capacity: 40 liter, Filter capacity: 4 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Change every 12 months		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 30	
Change every 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth 10W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30
Change every 12 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 12 months		

DIFFERENTIAL REAR LEADING HUB REDUCTIONS HD 7 Capacity: 12 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

DIFFERENTIAL REAR TRAILING HUB REDUCTIONS HL 7 Capacity: 12 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90



SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
HUB REDUCTIONS REAR HD 7 / I Capacity: 3,25 liter	-1L 7	

POWER TAKE OFF Capacity: 5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Syngear HS 75W-90	
Syngear no 75W-90	

RETARDER Telma CC

We are unable to give a standard recommendation for this component. Please contact our service department.

RETARDER Voith 115 H Capacity: 5,4 liter			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 30			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SCD 20W-20	Multifleet SCD 10W		

THROUGH SHAFT ASSEMBLY F Capacity: 3,5 liter	ID 7	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90



Syngear HS 75W-90			
PRODUCT RECOMMENDATION 1			
Normal		Moderate	
USE		CLIMATE	
TRANSMISSION MANUAL MB G 240-16 EPS (715.5) 16/2 Capacity: 14 liter, Capacity: 15 liter (+ oil cooler)			

TRANSMISSION SEMI-AUTOMATIC Capacity: 14 liter, Capacity: 15 liter (-		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Syngear HS 75W-90		

HYDRAULIC CAB TILT SYSTEM Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 15	
Change every 12 months	

USE	CLIMATE
Black reservoir cap	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 36 months	
USE	CLIMATE
Green reservoir cap	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	



POWER STEERING Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF-A

GREASE POINTS/NIPPLES STUB AXLE				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2			

Check every 12 months

GREASE POINTS/NIPPLES TRAILER COUPLING				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2			
Change every 12 months				

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2			
Change every 24 months		1		

COOLING SYSTEM Capacity: 45 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 11	
Change every 36 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.