## MERCEDES-BENZ (EU) ATEGO ATEGO 907 (4X2) (1998-2001)



| ENGINE OM904LA II/4<br>Capacity: 15,8 liter |                          |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal                                      |                          | Tropical                 |
| PRODUCT RECOMMENDATION 1                    |                          |                          |
| Multifleet SCD 40                           |                          |                          |
| Change every 12 months                      |                          |                          |
| USE   |                          | CLIMATE                  |
| Normal                                      |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2 |                          |
| Multifleet SHPD 20W-50                      | Multifleet SCD 30        |                          |
| Change every 12 months                      |                          |                          |
| USE   |                          | CLIMATE                  |
| Normal                                      |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Armado Synth 10W-40                         | Synfleet SHPD 10W-40     | Armado Synth 5W-30       |
| Change every 12 months                      |                          |                          |
| USE   |                          | CLIMATE                  |
| Normal                                      |                          | Arctic                   |
| PRODUCT RECOMMENDATION 1                    |                          |                          |
| Multifleet SCD 10W                          |                          |                          |
| Change every 12 months                      |                          |                          |

| DIFFERENTIAL REAR HYPOID IN Capacity: 6 liter | 1B HL2                   |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011                                  | Syngear TDL 75W-90       | Gearlube GL-5 80W-90     |
| Change every 12 months                        |                          |                          |

| TRANSMISSION MANUAL G 60-6<br>Capacity: 9 liter | 6/1                      |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                        | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Syngear HS 75W-90                               | Gearlube GL-4 80W        | Gearlube GL-4 80W-90     |
| Change every 12 months                          |                          | ·                        |

## MERCEDES-BENZ (EU) ATEGO ATEGO 907 (4X2) (1998-2001)



| HYDRAULIC CAB TILT SYSTEM |          |
|---------------------------|----------|
| USE                       | CLIMATE  |
| Normal                    | Moderate |
| PRODUCT RECOMMENDATION 1  |          |
| Perlus H 15               |          |
| Change every 12 months    |          |

| HYDRAULIC SYSTEM         |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Perlus H 15              |          |
| Change every 12 months   |          |

| HYDRAULIC CLUTCH SYSTEM  |          |  |
|--------------------------|----------|--|
| USE                      | CLIMATE  |  |
| Black reservoir cap      | Moderate |  |
| PRODUCT RECOMMENDATION 1 |          |  |
| Drauliquid-S DOT 4       |          |  |
| Change every 36 months   |          |  |
| USE                      | CLIMATE  |  |
| Green reservoir cap      | Moderate |  |
| PRODUCT RECOMMENDATION 1 |          |  |
| SP Fluid 3013            |          |  |

| POWER STEERING           |                          |          |  |
|--------------------------|--------------------------|----------|--|
| USE                      |                          | CLIMATE  |  |
| Normal                   |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |  |
| SP Matic 4026            | SP Matic 2032            |          |  |

| GREASE POINTS/NIPPLES    |                          |          |  |
|--------------------------|--------------------------|----------|--|
| USE                      |                          | CLIMATE  |  |
| Normal                   |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |  |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |          |  |

## MERCEDES-BENZ (EU) ATEGO ATEGO 907 (4X2) (1998-2001)



| GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal                                     |                          | Moderate |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2 |          |
| Q5 MP Calcep Grease EP 2                   | MP Lithep Grease EP 2    |          |
| 01 04 11                                   |                          |          |

Change every 24 months

| COOLING SYSTEM Capacity: 19 liter |                          |          |
|-----------------------------------|--------------------------|----------|
| USE                               |                          | CLIMATE  |
| Normal                            |                          | Moderate |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15+                    | Coolant SP 11            |          |
| Change every 36 months            |                          | ,        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.