

MERCEDES-BENZ (EU) PUBLIC-SERVICE-BUSES CITARO (O 530) OM457HLA (1996-2007)



ENGINE OM457hLA
Capacity: 28 liter

USE	CLIMATE
City bus	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Check every 12 months, change every 60000 km/ 24 months

DIFFERENTIAL REAR
Capacity: 18 liter

USE	CLIMATE
City bus	Moderate

PRODUCT RECOMMENDATION 1		
Unigear HS GL-3/GL-5 80W-90		

Check every 12 months, change every 120000 km

TRANSMISSION AUTOMATIC 4/1
Capacity: 26 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 12 months, change every 120000 km/ 36 months

TRANSMISSION AUTOMATIC ZF 6HP502/592 6/1

We are unable to give a standard recommendation for this component. Please contact our service department.

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Check every 12 months

CENTRAL LUBRICATION SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

MERCEDES-BENZ (EU) PUBLIC-SERVICE-BUSES CITARO (O 530) OM457HLA (1996-2007)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Check every 12 months

GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

Change every 30000 km/ 6 months

WHEEL BEARINGS REAR OIL LUBRICATED

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 120000 km/ 12 months

COOLING SYSTEM

Capacity: 47 liter, Capacity: 50-55 liter (with roofheater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 12 months, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.