

# MERCEDES-BENZ (EU) PUBLIC-SERVICE-BUSES INTEGRO L EURO 3 OM457HLA (1996-2006)



**ENGINE** OM457hLA Euro 3  
Capacity: 30,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet MSP 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth LSP 10W-40</b>

**DIFFERENTIAL REAR**  
Capacity: 18 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 12 months, change every 120000 km*

**TRANSMISSION AUTOMATIC 4/1**  
Capacity: 26 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Check every 12 months, change every 120000 km/ 36 months*

**TRANSMISSION AUTOMATIC ZF Ecomat 6/1**

We are unable to give a standard recommendation for this component. Please contact our service department.

**POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 4026</b>	<b>SP Matic 2032</b>	

*Check every 12 months*

**CENTRAL LUBRICATION SYSTEM**

We are unable to give a standard recommendation for this component. Please contact our service department.

# MERCEDES-BENZ (EU) PUBLIC-SERVICE-BUSES INTEGRO L EURO 3 OM457HLA (1996-2006)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	
<i>Check every 12 months</i>		

## GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	
<i>Change every 30000 km/ 6 months</i>		

## WHEEL BEARINGS REAR OIL LUBRICATED

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	
<i>Change every 120000 km/ 12 months</i>		

## COOLING SYSTEM

Capacity: 47 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 11</b>		
<i>Check every 12 months, change every 36 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.