

# MERCEDES-BENZ (EU) UNIMOG UNIMOG U 3000 (437) EURO 4 (2006-2009)



**ENGINE OM904LA**  
Capacity: 15,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2             | PRODUCT RECOMMENDATION 3       |
|-------------------------------------|--------------------------------------|--------------------------------|
| <b>Armado Synth LSP Ultra 5W-30</b> | <b>Armado Synth LSP Ultra 10W-40</b> | <b>Armado Synth LSP 10W-40</b> |

*Change every 1200 hours/ 24 months*

**DIFFERENTIAL FRONT**  
Capacity: 2,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |  |
|--------------------------|---------------------------|--|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |  |

*Check every 24 months/ 1200 hours, change every 2400 hours/ 60 months*

**DIFFERENTIAL REAR**  
Capacity: 2,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |  |
|--------------------------|---------------------------|--|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |  |

*Check every 24 months/ 1200 hours, change every 2400 hours/ 60 months*

**POWER TAKE OFF**  
Capacity: 4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    |  |  |
|-----------------------------|--|--|
| <b>Syngear MT/LD 75W-80</b> |  |  |

*Check every 24 months/ 1200 hours, change every 2400 hours/ 60 months*

**TRANSFERBOX/P.T.O.**  
Capacity: 2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    |  |  |
|-----------------------------|--|--|
| <b>Syngear MT/LD 75W-80</b> |  |  |

*Check every 24 months/ 1200 hours, change every 2400 hours/ 60 months*

# MERCEDES-BENZ (EU) UNIMOG UNIMOG U 3000 (437) EURO 4 (2006-2009)



## TRANSMISSION MANUAL 718.841 8/6

Capacity: 11 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Syngear MT/LD 75W-80***Check every 24 months/ 1200 hours, change every 2400 hours/ 60 months*

## HYDRAULIC SYSTEM

Capacity: 28 liter (Dry fill), Capacity: 25 liter (Service fill)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 20W-50***Change every 2400 hours/ 36 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40***Change every 2400 hours/ 36 months*

## HYDRAULIC BRAKE SYSTEM ABS

Capacity: 2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-S DOT 4***Change every 12 months*

## HYDRAULIC CLUTCH SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-S DOT 4***Change every 12 months*

# MERCEDES-BENZ (EU) UNIMOG UNIMOG U 3000 (437) EURO 4 (2006-2009)



## POWER STEERING

Capacity: 3,2 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 4026</b>     | <b>SP Matic 2032</b>     | <b>ATF-A</b>             |

Check every 24 months/ 1200 hours

## GREASE POINTS/NIPPLES OTHERS

| USE                             |                              | CLIMATE  |
|---------------------------------|------------------------------|----------|
| Normal                          |                              | Moderate |
| PRODUCT RECOMMENDATION 1        | PRODUCT RECOMMENDATION 2     |          |
| <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |          |

Check every 24 months/ 1200 hours

## COOLING SYSTEM

Capacity: 26 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 11</b>     | <b>Coolant SP 12 EVO</b> |          |

Check every 12 months, change every 36 months

## WHEEL BEARINGS OIL LUBRICATED

Capacity: 0,7 liter

| USE                      |                           | CLIMATE  |
|--------------------------|---------------------------|----------|
| Normal                   |                           | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |          |

Check every 24 months/ 1200 hours, change every 2400 hours/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.