MERITOR SINGLE REDUCTION AXLES -TANDEM AXLES SR-270/280, RT-, RP-48-380



DIFFERENTIAL REAR LEADING Capacity: 26 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140			
Check every 4800 km/ 1 months, change every 160000 km				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90		
Check every 4800 km/ 1 months, change every 160000 km				
USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				
SP Gear 5015				
Check every 4800 km/ 1 months, change every 160000 km				

DIFFERENTIAL REAR TRAILING Capacity: 26 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 4800 km/1 months, change every 160000 km

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 4800 km/1 months, change every 160000 km

use Normal		climate Cold		
PRODUCT RECOMMENDATION 1				
SP Gear 5015				
Check every 4800 km/ 1 months, change every 160000 km				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.