PRODUCT RECOMMENDATION

PACCAR MX SERIES MX-13 EPA 10 (2012-2015)

ENGINE Paccar MX-13
Capacity: 40 liter

USE		CLIMATE
Severe duty		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		

Change every 25000 miles/ 12 months/ 800 hours

USE		CLIMATE
Line haul, idle time > 20%		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		

Change every 40000 miles/ 12 months/ 1200 hours

USE		CLIMATE
Line haul, idle time < 20% and engine software level ESB E070 or higher		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	**Dieselfleet MSP 10W-30**	

Change every 60000 miles/ 12 months/ 1200 hours

USE		CLIMATE
Line haul, idle time < 20%		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		

Change every 60000 miles/ 12 months/ 1200 hours

USE		CLIMATE
Line haul, idle time > 20% and engine software level ESB E070 or higher		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	**Dieselfleet MSP 10W-30**	

Change every 40000 miles/ 12 months/ 1200 hours

USE		CLIMATE
Severe duty, engine software level ESB E070 or higher		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	**Dieselfleet MSP 10W-30**	

Change every 25000 miles/ 12 months/ 800 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

PACCAR MX SERIES MX-13 EPA 10 (2012-2015)

COOLING SYSTEM
Capacity: 53-57 liter

USE		CLIMATE
On-road use		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**
Change every 750000 miles/ 72 months/ 22000 hours		

USE		CLIMATE
Off-road use		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**
Change every 96 months/ 15000 hours		

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367