

PACCAR MX SERIES MX 485 (2010-2012)

ENGINE Paccar MX
Capacity: 40 liter

| USE | CLIMATE |
|--|----------|
| Fuel economy > 6 MPG and GVW < 80000 lbs | Moderate |

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40*Change every 40000 miles/ 12 months/ 1200 hours*

| USE | CLIMATE |
|--|---------|
| Fuel economy > 6 MPG and GVW < 80000 lbs | Arctic |

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30*Change every 40000 miles/ 12 months/ 1200 hours*

| USE | CLIMATE |
|---|----------|
| Fuel economy < 6 MPG or GVW > 80000 lbs | Moderate |

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40*Change every 25000 miles/ 12 months/ 800 hours*

| USE | CLIMATE |
|---|---------|
| Fuel economy < 6 MPG or GVW > 80000 lbs | Arctic |

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30*Change every 25000 miles/ 12 months/ 800 hours*

| USE | CLIMATE |
|------------|----------|
| Vocational | Moderate |

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40*Change every 25000 miles/ 12 months/ 800 hours*

| USE | CLIMATE |
|------------|---------|
| Vocational | Arctic |

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30*Change every 25000 miles/ 12 months/ 800 hours*

PACCAR MX SERIES MX 485 (2010-2012)**COOLING SYSTEM**

Capacity: 53-57 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| On-road use | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Change every 750000 miles/ 72 months/ 22000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Off-road use | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

*Change every 96 months/ 15000 hours***SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)**

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.